

screen-mate

High Alkaline Dishmachine Detergent

Product Properties

COLOR: White Powder ODOR: Mild pH (1%): 14 FOAMING: None to Flash DETERGENCY: Excellent HARD WATER TOLERANCE: Excellent

Description

This high performance, dishmachine detergent is highly concentrated for maximum economy. It routinely powers away the most difficult food soils including grease, fats, oils, protein and food stains. It is ideal and safe for use on all fine china, glass, crystal, silver, stainless, copper, aluminum and alkali resistant plastic tableware. Corrosion inhibited to protect delicate machine parts. Inhibits lime and scale buildup. Packaged in an auto-feed capsule for optimum use-control and safety.

Features...Benefits

Highly Concentrated	. Economical
Fast Acting	Labor Saving
Corrosion Inhibited	Protects Machine Parts
Hard Water Tolerant	. Improved Performance
Prevents Limescale Build-Ups	Labor Saving

Directions

This product is not designed for use on soft metals such as Aluminum or Pewter. Soft metals or delicate ware items should be washed using an appropriate metal safe detergent. This product is for use in capsule feeder dispenser only. DO NOT use this product in conventional water-filled reservoir systems. Remove the cover from the capsule and turn it over, placing it in the dispenser screen side down. DO NOT REMOVE SCREEN CAP FROM THE CAPSULE. Remove and replace capsule when completely empty by turning screen side up and using cover from new capsule to close empty capsule. Wash hands thoroughly after handling product. Consult your Service Representative for specific information on use of this product in your application.

Safety Information

KEEP OUT OF REACH OF CHILDREN DANGER

CORROSIVE. CAUSES BURNS TO SKIN AND EYES. CONTAINS SODIUM HYDROX-IDE AND ALKALINE DETERGENT BUILDERS. Avoid contact with skin and eyes. In case of contact with eyes, immediately flush with plenty of water for 15 minutes and seek immediate medical attention. For skin, flush with water followed by a mild vinegar solution. Seek medical attention if irritation persists.

Letter of guarantee available upon request.

151105-0113 © INTERCON 2015 REFER TO PRODUCT LABEL AND SDS FOR ADDITIONAL INFORMATION

1100 Central Industrial Dr. St. Louis, Missouri, 63110

toll free: 800 325 9218 main: 314 771 6600 fax: 314 771 6608

www.interconchemical.com

